

GELEST, INC.

11 East Steel Rd. Morrisville, PA 19067

Phone: (215) 547-1015

MATERIAL SAFETY
DATA SHEET

EMERGENCY TELEPHONE
CHEMTREC: 1-800-424-9300

NAME USED ON LABEL: **CHLOROSILANE 95% - SIC2414.0**

CHEMICAL NAME: CHLOROSILANE

SYNONYMS: MONOCHLOROSILANE; TRIHYDROGENCHLOROSILANE

CHEMICAL FAMILY: CHLOROSILANE

FORMULA: H₃ClSi

HMIS CODES HEALTH: 4 FLAMMABILITY: 4 REACTIVITY: 3

INGREDIENTS

IDENTITY	CAS NO.	%	TLV
CHLOROSILANE	13465-78-6	>90	not established
SILANE	7803-62-5	<5	(ACGIH TLV for silane: 5ppm TWA)
DICHLOROSILANE	4109-96-0	<5	not established

PHYSICAL DATA

Boiling Point: -30.4°C

Specific Gravity: 1.145 at -113°C

Vapor Density (air=1): 2.3

% volatiles: 100%

Molecular Weight: 66.56

Appearance & Color: Colorless, pyrophoric gas with disagreeable odor of hydrogen chloride

Freezing Point: -118°C

Vapor Pressure, 50°: 125.3mm

Solubility in water: reacts

Evaporation rate: not determined

FIRE & EXPLOSION DATA

Chlorosilane spontaneously ignites on contact with air.

Flash Point, CC : -90°C (-130°F) Autoignition Temp.: <20°C(68°F)

Flammability Limits LEL: 4.5% UEL: 94-98%

Extinguishing Media: If unable to stop the flow of gas, chlorosilane should be allowed to burn until consumed. Secondary fires may be extinguished with alcohol resistant foam, carbon dioxide, dry chemical. Use of high expansion foam (100:1) is recommended to cover flames.

Special Fire Fighting Procedures: Chlorosilane should be allowed to burn until consumed.

Excessive pressure may develop in gas cylinders exposed to fire-heated chlorosilane may explode on contact with air. Cool cylinders and surroundings with water from a suitable distance.

Do not breathe fumes or inhale vapors.

Unusual Fire and Explosion Hazards: Irritating fumes and organic acid vapors may develop when material is exposed to water or open flame.

-1-(SIC2414.0)

ENVIRONMENTAL INFORMATION

Spill response: Stop flow of gas if possible. Evacuate area. The potential exists for spontaneous ignition and explosion. Allow vapors to disperse. Ventilate area.

Recommended Disposal: Incinerate. Follow all chemical pollution control regulations.

HEALTH HAZARD DATA

Eye Contact: Will cause immediate or delayed severe burns. At levels below the flammability limit, silane is expected to affect the eyes by absorption and deposition of silicon dioxide, causing severe irritation and possible corneal damage.

Skin contact: May produce irritation or contact dermatitis.

Inhalation: Inhalation of vapors will irritate the respiratory tract. Overexposure may produce severe tissue damage.

Inhalation Toxicity- rat, LC50: 4257ppm (1H)

Oral Toxicity: not determined

Chronic Toxicity: There are no known chronic effects related to this compound.

SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention.

SKIN: Wash with soap and water.

INHALATION: Move exposed individual to fresh air. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. Get medical attention.

REACTIVITY DATA

Stability: Stable in sealed cylinders stored under a dry inert atmosphere.

Conditions to avoid: Avoid contact with heat, sparks or open flame.

Incompatibility (materials to avoid): Reacts with oxygen in air, igniting spontaneously. Mixtures with mercury explode when shaken in the presence of air. Platinum, platinum and iron salts and other Lewis acids can cause generation of flammable hydrogen gas. Avoid contact with alcohols, acids, oxidizers.

Hazardous decomposition products: Silicon dioxide, hydrogen chloride.

-2-(SIC2414.0)

SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV air-supplied or combination organic vapor/acid gas respirator.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency shower should be available.

OTHER PRECAUTIONS

For research and industrial use only.

Storage and Handling: Store in sealed cylinders in isolated area.

Containers and transfer lines require grounding during use.

Systems utilizing silane that do not involve complete consumption of chlorosilane should be equipped with burn boxes. See- Book of SEMI Standards, Facilities Standards and Safety Guidelines, Mountain View, CA, Semiconductor Equipment and Materials Int'l, 1993

TRANSPORTATION

DOT SHIPPING NAME: LIQUIFIED GAS GAS, TOXIC, FLAMMABLE N.O.S. (CHLOROSILANE)

DOT HAZARD CLASS: 2.3 SUB: 2.1,8

DOT LABEL: TOXIC, FLAMMABLE GAS, CORROSIVE

DOT ID No: UN3309

Transport by air is forbidden.

Prepared by safety and environmental affairs ISSUE DATE SIC2414.0: 12/15/11

SUPERSEDES: 2/1/07

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

-3-(SIC2414.0)

© 2011 Gelest Inc. Morrisville, PA 19067