

Safety Data Sheet AKL459
Date of issue: 03/11/2016 Version: 1.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance
Physical state : Solid

Substance name : LITHIUM ISOPROPOXIDE

Product code : AKL459
Formula : C3H7LiO

Synonyms : 2-PROPANOL, LITHIUM SALT; LITHIUM ISOPROPYLATE

Chemical family : METAL ALCOHOLATE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Chemical intermediate

For research use only

1.3. Details of the supplier of the safety data sheet

GELEST, INC.

11 East Steel Road Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Sol. 2 H228 Skin Corr. 1B H314 Eye Dam. 1 H318

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





GHS02

GHS05

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H228 - Flammable solid

H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS-US) : P280 - Wear protective gloves/protective clothing/eye protection/face protection

P210 - Keep away from heat, open flames, sparks. - No smoking

P240 - Ground/bond container and receiving equipment

P241 - Use explosion-proof electrical equipment

P260 - Do not breathe dust

P264 - Wash hands thoroughly after handling

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a doctor

P321 - Specific treatment (see first aid instructions on this label)

P363 - Wash contaminated clothing before reuse

P370+P378 - In case of fire: Use dry chemical, dry soda ash or dry sodium chloride to

extinguish

P405 - Store locked up

P501 - Dispose of contents/container to licensed waste disposal facility

03/11/2016 EN (English US) SDS ID: **AKL459** Page 1

Safety Data Sheet

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Substance type : Mono-constituent

Name : LITHIUM ISOPROPOXIDE

CAS No : 2388-10-5

Name	Product identifier	%	GHS-US classification
Lithium isopropoxide	(CAS No) 2388-10-5	95 - 100	Flam. Sol. 2, H228 Skin Corr. 1B. H314
			Eye Dam. 1, H318

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek

medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get immediate medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes severe skin burns and eye damage.

Symptoms/injuries after inhalation : Inhalation will cause sneezing, irritation and burns.

Symptoms/injuries after skin contact : Causes (severe) skin burns. If skin and air are dry, powder on skin may not cause irritation or

burns. Worker will notice a slippery feeling on washing. However, if moisture is present, the powder can cause severe burns.

Symptoms/injuries after eye contact : Causes serious eye damage.
Symptoms/injuries after ingestion : May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical. Dry soda ash. Dry sodium chloride.

Unsuitable extinguishing media : Do not use water or carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable solid. Irritating fumes and caustic vapors may develop when material is exposed to

elevated temperatures or open flame.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Protect against caustic dust, smoke and

water.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Avoid contact with skin and eyes. Do not breathe dust. Wear pressure demand self-contained breathing apparatus with full facepiece and full protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

03/11/2016 EN (English US) SDS ID: **AKL459** 2/7

Safety Data Sheet

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with

proper protection. For further information refer to section 8: "Exposure controls/personal

protection".

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams.

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or

shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Precautions for safe handling : Avoid contact with skin and eyes. Do not breathe dust. Avoid dust formation. Ground containers

when handling powder. Use only outdoors or in a well-ventilated area. Use only non-sparking

tools.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Use explosion-proof electrical equipment.

Storage conditions : Keep container tightly closed. Store locked up. Store under dry nitrogen or argon in sealed

containers.

Incompatible materials : Acids. Alcohols. Carbon dioxide. Esters. Halogens. Ketones. Moist air. Oxidizing agent. Water.

Storage area : Store in a well-ventilated place. Store away from heat.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

Personal protective equipment : Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be

available in the immediate vicinity of any potential exposure.

Hand protection : Neoprene or nitrile rubber gloves.

Eye protection : Chemical goggles or face shield. Contact lenses should not be worn.

Skin and body protection : Wear suitable protective clothing. Long-sleeved fire-resistant lab uniform or coverall is

recommended.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended. NIOSH-certified caustic organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

: Solid Physical state Appearance : Powder. Molecular mass : 66.03 g/mol Color White to off-white. No data available Odor Odor threshold No data available Refractive index No data available Ha No data available Relative evaporation rate (butyl acetate=1) No data available Melting point : No data available Freezing point : No data available

03/11/2016 EN (English US) SDS ID: **AKL459** 3/7

Safety Data Sheet

Boiling point : No data available : No data available Flash point Auto-ignition temperature : No data available Decomposition temperature No data available Flammability (solid, gas) Flammable solid Vapor pressure No data available Relative vapor density at 20 °C No data available No data available Relative density Solubility Reacts with water. No data available Log Pow Log Kow : No data available No data available Viscosity, kinematic No data available Viscosity, dynamic Explosive properties No data available Oxidizing properties : No data available : No data available **Explosion limits**

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under nitrogen or argon in sealed containers.

10.3. Possibility of hazardous reactions

Material decomposes slowly in contact with moist air and rapidly in contact with water.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Acids. Alcohols. Carbon dioxide. Esters. Halogens. Ketones. Moist air. Oxidizing agent. Water.

10.6. Hazardous decomposition products

Caustic organic vapors. Isopropanol. Lithium hydroxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified Specific target organ toxicity (repeated : Not classified

exposure)

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : Inhalation will cause sneezing, irritation and burns.

Symptoms/injuries after skin contact : Causes (severe) skin burns. If skin and air are dry, powder on skin may not cause irritation or

burns. Worker will notice a slippery feeling on washing. However, if moisture is present, the

powder can cause severe burns.

Symptoms/injuries after eye contact : Causes serious eye damage. Symptoms/injuries after ingestion : May be harmful if swallowed.

Reason for classification : Expert judgment

03/11/2016 EN (English US) SDS ID: **AKL459** 4/7

Safety Data Sheet

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on ozone layer : No additional information available

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to licensed waste disposal facility.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT) : 2925 DOT NA no. UN2925

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Flammable solids, corrosive, organic, n.o.s.

(LITHIUM ISOPROPOXIDE)

Class (DOT) : 4.1 - Class 4.1 - Flammable Solid 49 CFR 173.124

Hazard labels (DOT) : 4.1 - Flammable solid

8 - Corrosive



DOT Symbols : G - Identifies PSN requiring a technical name

Packing group (DOT) : II - Medium Danger

DOT Packaging Exceptions (49 CFR 173.xxx) : None
DOT Packaging Non Bulk (49 CFR 173.xxx) : 212
DOT Packaging Bulk (49 CFR 173.xxx) : 242

14.3. Additional information

Emergency Response Guide (ERG) Number : 134

Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel

carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger

vessels in which the limiting number of passengers is exceeded

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 15 kg

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 50 kg

CFR 175.75)

03/11/2016 EN (English US) SDS ID: **AKL459** 5/7

Safety Data Sheet

SECTION 15: Regulatory information

15.1. US Federal regulations

LITHIUM ISOPROPOXIDE (2388-10-5)				
TSCA Exemption/Exclusion	CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not partition in the United States.			

Lithium isopropoxide (2388-10-5)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

Lithium isopropoxide (2388-10-5)

Listed on ELINCS (European List of Notified Chemical Substances)

15.3. US State regulations

ITHIUM ISOPROPOXIDE(2388-10-5)		
U.S California - Proposition 65 - Carcinogens List	No	
U.S California - Proposition 65 - Developmental Toxicity	No	
U.S California - Proposition 65 - Reproductive Toxicity - Female	No	
U.S California - Proposition 65 - Reproductive Toxicity - Male	No	

Lithium isopropoxide (2388-10-5)

U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

SECTION 16: Other information

Abbreviations and acronyms

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development.

Full text of H-phrases::

H228	Flammable solid
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage

HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 2 Moderate Hazard Physical : 1 Slight Hazard

Prepared by safety and environmental affairs.

SDS US (GHS HazCom 2012) - Custom


According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

03/11/2016 EN (English US) SDS ID: **AKL459** 6/7

Safety Data Sheet

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2016 Gelest Inc. Morrisville, PA 19067



03/11/2016 EN (English US) SDS ID: **AKL459** 7/7