

GELEST, INC.

11 East Steel Rd. Morrisville, PA 19067
Phone: (215) 547-1015

MATERIAL SAFETY
DATA SHEET

EMERGENCY TELEPHONE
CHEMTREC: 1-800-424-9300

NAME USED ON LABEL: **SODIUM 2,4-PENTANEDIONATE - AKS770**

CHEMICAL NAME: SODIUM 2,4-PENTANEDIONATE

SYNONYMS: SODIUM ACETYLACETONATE

CHEMICAL FAMILY: METAL DIKETONATE

FORMULA: C₅H₇O₂Na

HMIS CODES HEALTH: 3 FLAMMABILITY: 2 REACTIVITY: 1

IDENTITY	INGREDIENTS			OSHA PEL
	CAS NO.	%	TLV	
SODIUM 2,4-PENTANEDIONATE	86891-03-4	>95%	not established	

Boiling Point: N/A

Specific Gravity: N/A

Vapor Density, air =1: NA

% volatiles: <3

Molecular Weight: 122.09

Appearance & Color: Off-white to light- brown powder.

Melting Point: 210°-decomposes

Vapor Pressure: not determined

Solubility in water: soluble

Evaporation rate: N/A

Other: N/A

FIRE & EXPLOSION DATA

Flash Point, COC: NA

Autoignition Temp.: not determined

Flammability Limits- LEL: NA UEL: NA

Extinguishing Media: Dry chemical extinguisher, dry soda ash, or dry sodium chloride.

Special Fire Fighting Procedures: Protect against caustic dust, smoke and water. Wear pressure demand self-contained breathing apparatus with full facepiece and full protective clothing.

Unusual Fire and Explosion Hazards: Irritating fumes and caustic vapors may develop when material is exposed to elevated temperatures or open flame.

ENVIRONMENTAL INFORMATION

Spill response: Ventilate area. Eliminate ignition sources. Scoop material into a dry metal container and cover loosely.

Recommended disposal: Incinerate. Follow all chemical pollution control regulations.

HEALTH HAZARD DATA

Eye Contact: Sodium pentanedionate may cause immediate or delayed burns to the eyes.

Skin contact: May cause irritation and caustic burns.

Inhalation: Inhalation will cause sneezing, irritation and burns.

Oral Toxicity: not determined

Inhalation Toxicity: not determined

SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes, holding eyes open. Get medical attention.

SKIN: Immediately shake or brush off any loose material, then flush with water for at least fifteen minutes.

INHALATION: Move exposed individual to fresh air. Administer oxygen if needed. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions.

REACTIVITY DATA

Stability: Stable under nitrogen or argon in sealed containers.

Conditions to avoid: Material decomposes slowly in contact with moist air and rapidly in contact with water.

Hazardous decomposition products: Sodium hydroxide and caustic organic vapors.

SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV, a NIOSH approved particulate filter-type respirator should be worn.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency shower should be available. Launder clothing before reuse.

OTHER PRECAUTIONS

For research and industrial use only.

Storage and Handling: Store under dry nitrogen or argon in sealed containers.

TRANSPORTATION

DOT SHIPPING NAME: CHEMICALS NOI

DOT HAZARD CLASS: NONE REQUIRED

DOT LABELS: NONE REQUIRED

DOT ID No: NONE REQUIRED

Prepared by safety and environmental affairs

ISSUE DATE AKS770: 2/18/03

SUPERSEDES: 5/10/01

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore.